



# **Please Read & Follow**

To avoid issues in Tech with the 2-cycle fuel & oil mixture please consider following one of the procedures below.

## **➤ *Mixing the fuel & oil in your new VP MS98L can***

- *Pour all of the Elf oil into the can*
- *Rinse out the Elf oil bottle with some of your new VP MS98L fuel and place back in can*
- *Shake/mix the fuel vigorously to assure it is completely mix*
- *Before putting the mixed fuel in your Kart the 1<sup>st</sup> time remove any leftover fuel from the tank that has only been used for race fuel (No pump gas)*

## **➤ *Mixing the VP MS98L fuel & oil in your fuel jug***

- *Use a clean dry fuel jug that does not have any other fuel in it and has only been used for race fuel (No Pump Gas)*
- *Pour the Elf oil into your fuel jug*
- *Rinse out the Elf oil bottle with some of the VP MS 98 fuel and place back in your fuel jug*
- *If you are mixing all 5 gallons consider pouring 4 – 4 ½ gallons into your fuel jug and vigorously shake/mix*
- *Add the remaining fuel to your jug and again shake/mix*
- *Before putting the mixed fuel in your Kart the 1<sup>st</sup> time remove any leftover fuel from the tank that has only been used for race fuel*

***It is very important that you rinse out your Elf oil bottle as our Fuel Tester will identify this and send up a red flag!***